

## SPECIFICATIONS

### PERFORMANCE

Engine power at 2,250 rpm	50 (B.S) hp*
Torque at 1,400 engine rpm	172 Nm
PTO power at rated engine speed	44 hp**

\* Certified to BS.AU 141a: (1971)

\*\* Manufacturer's estimate

### ENGINE

Type	Diesel /AD 3.1524
No. of cylinders	3
Injection	Direct
Bore	91.5 mm
Stroke	127.0 mm
Capacity (litres)	2.5
Compression ratio	16.5:1
Aspiration	Natural
Starting aid	Thermostart
Throttle control	Hand and foot
Cooling	Water
Air Cleaner Type	Oil bath
Air Pre-Cleaner	Over bonnet
Fuel filter	Dual, high capacity
Exhaust	Vertical

### CLUTCH

Type	Dual clutch
Diameter	305x254 mm

### TRACK ADJUSTMENT

Front	1,245 - 1,854 mm
Rear	1,219 - 1,930 mm

### ELECTRICS

Voltage	12V, Negative Earth
Battery	118 Ah
Starter Motor	2.2 kW
Alternator	32 Amp.

### FRONT AXLE

Type	Box Section, Adjustable
------	-------------------------

### POWER TAKE OFF

Type	Live
Engine speed at 540 PTO rpm	1,789 rpm
Shaft diameter	35 mm
No. of splines	6

### HYDRAULICS

Functions	Draft control, Position control, Response Control, Constant pumping
Pump Type	Reciprocating Ferguson Pump
Oil Flow	16l/ min
Pressure	19.2 MPa
Lift capacity with lower links horizontal	1,415 kg
Lower links	With Cat. 1 & 11 interchangeable balls

### STEERING

Steering	Manual
----------	--------

### REAR AXLE AND BRAKES

Brake Type	Outboard drum brakes
Actuation	Mechanical, Independent or locked together
Parking Brake	Hand lever operated
Differential lock	Mechanical

### TYRES

Front	5.50 - 16 (8PR)
Rear	12.4/11-24 (12 PR)

### WEIGHTS AND DIMENSIONS

(With 5.50-16 front & 12.4 / 11-24 rear wheel and with full fuel, oil and water)

Weight	
Gross Weight	1,515 kg
Dimensions	
Wheel base	1,892mm
Overall length	3,240mm
Overall width (min)	1,604mm
Height	
Over exhaust	1,905mm
Over steering wheel	1,386mm
Turning circle	
With brakes	5,710mm
Without brakes	6,277mm
Ground clearance (Under gear box)	295 mm

### TRANSMISSION

Type	Sliding spur
Number of gears	8 forward 2 reverse

Road speed at 2,250 engine rpm with 12.4/11-28 rear tyres

Gear	Speed (km/hr)
Forward 1 (first low)	2.3
Forward 2	3.4
Forward 3	4.7
Forward 4	6.3
Forward 5 (first high)	9.3
Forward 6	13.6
Forward 7	18.6
Forward 8	25.0
Reverse 1 (low)	3.2
Reverse 2 (high)	12.7

### CAPACITIES

Fuel Tank	50L
Engine sump	6.96L
Cooling system	11.7L
Hydraulic system	33.0L
Steering box	0.75L
Oil bath air - cleaner	0.65L