

MF 240_{2WD}

SPECIFICATIONS

PERFORMANCE

Engine power at 2,250 rpm Torque at 1,400 engine rpm PTO power at rated engine speed

*Certified to BS.AU 141a: (1971)

Manufacturer's estimate

ENGINE

Type
No. of cylinders
Injection
Bore
Stroke
Capacity (litres)
Compression ratio
Aspiration
Starting aid
Throttle control
Cooling
Air Cleaner Type
Air Pre-Cleaner
Fuel filter
Exhaust

50 (B.S) hp* 172 Nm 44 hp**

Diesel /AD 3.1524

Direct

2.5

16.5:1

Natural

Water

Oil bath

Vertical

Thermostart

Hand and foot

Over bonnet

Dual, high capacity

91.5 mm

127.0 mm

POWER TAKE OFF

Type
Engine speed at 540 PTO rpm
Shaft diameter
No. of splines

Live 1,789 rpm 35 mm 6

HYDRAULICS

Functions

Pump Type
Oil Flow

Pressure Lift capacity with lower links horizontal Lower links

Draft control,
Position control,
Response Control,
Constant pumping
Reciprocating
Ferguson Pump
16k/ min
19.2 MPa
1,415 kg
With Cat. 1 & 11
interchangeable

balls

WEIGHTS AND DIMENSIONS

1,650 kg

1,892mm

3,260mm

1,651mm

2.145mm

1,410mm

5,560mm

(With 6.00–16 front & 12.4 / 11–28 rear wheel and with full fuel, oil and water)

Weight
Gross Weight
Dimensions
Wheel base
Overall length
Overall width (min)
Height
Over exhaust
Over steering wheel
Turning circle
With brakes
Without brakes

Without brakes 6,200mm
Ground clearance
(Under gear box) 338 mm

CLUTCH

Type Diameter Dual clutch 305x254 mm STEERING

Steering

TRANSMISSION

Type Sliding spur Number of gears 8 forward 2 reverse

Road speed at 2,250 engine rpm with 12.4/11-28 rear tyres

Speed (km/hr) Gear Forward 1 (first low) 2.5 Forward 2 3.7 5.0 Forward 3 Forward 4 6.7 Forward 5 (first high) 10.0 Forward 6 14.7 Forward 7 20.1 Forward 8 27.0 Reverse 1 (low) 34 Reverse 2 (high) 13.6

TRACK ADJUSTMENT

Front Rear 1,245 - 1,854 mm 1,219 - 1,930 mm

REAR AXLE AND BRAKES

Brake Type Actuation

Parking Brake Differential lock Outboard drum brakes Mechanical, Independent or locked together Hand lever operated Mechanical

ELECTRICS

Voltage Battery Starter Motor Alternator 12V, Negative Earth 118 Ah 2.2 kW 32 Amp.

FRONT AXLE

Туре

Box Section, Adjustable

TYRES

Front 6.00 - 16 (6PR) Rear 12.4/11-28 (6 PR)

CAPACITIES

 Fuel Tank
 47.5L

 Engine sump
 6.8L

 Cooling system
 10.2L

 Hydraulic system
 33.0L

 Steering box
 0.9L

 Oil bath air - cleaner
 0.65L