

PNEUMATIC SEEDER (TINE SHARED) HVM

Specifications	Unit	HVM 4	HVM 5	HVM 6	HVM 8
Number Of Units	Pcs	4	5	6	8
(A) Total Length	cm	200	200	200	200
(B) Total Height	cm	160	160	160	160
(C) Total Width	cm	300	300	380	600
(D) Distance Between Rows	cm	25x90	25x90	25x90	25x90
Seed Capacity	lt	60 x 4	60 x 5	60 x 6	60 x 8
Fertilizer Case Vol.	lt	170 x 2	170 x 2	230 x 2	170 x 4
Rpm	d/d	540	540	540	540
Weight Without Fertilizer Hopper	kg	700	850	1000	1300
Weight With Fertilizer Hopper	kg	950	1100	1250	1500
Tyre Dimension	Inch	500 x 15	500 x 15	500 x 15	500 x 15
Power Requirement	hp	60	70	80	100



This machine which is called pneumatic precision sowing machine, is an agricultural machine which is driven only by cardan shaft and PTO shaft of the tractor and works with hydraulic lifting unit of the tractor and universal 3-point hanging system.

You can perform precision sowing and sow different kinds of seeds into all kinds of cultivated soil types with this equipment. Sowing machine operates with the help of a pneumatic system and can be equipped with various accessories such as additional sowing units such as a fertilizer tank. The most important feature of the sowing machine is the ease of use as well as the simplicity of its design.

Sowing unit ensures that all kinds of seeds can be sown one by one in every soil condition due to double disc for maximum efficiency, ie. without wasting seeds.